

US006468222B1

(12) United States Patent Mault et al.

(10) Patent No.: US 6,468,222 B1

(45) **Date of Patent:** Oct. 22, 2002

(54) METABOLIC CALORIMETER EMPLOYING RESPIRATORY GAS ANALYSIS

(75) Inventors: James R. Mault, Evergreen, CO (US); Edwin M. Pearce, Jr., San Francisco, CA (US); Theodore W. Barber, Belmont, CA (US); Craig M. Lawrence, Menlo Park, CA (US); Timothy J. Prachar, Palo Alto, CA (US); Jeffrey C. Weintraub, San Jose,

CA (US); **Kevin S. Nason**, Mountain View, CA (US)

(73) Assignee: HealtheTech, Inc., Golden, CO (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 11 days.

(21) Appl. No.: 09/630,398

(22) Filed: Aug. 2, 2000

Related U.S. Application Data

- (60) Provisional application No. 60/146,898, filed on Aug. 2, 1999, provisional application No. 60/155,035, filed on Sep. 20, 1999, provisional application No. 60/219,241, filed on Jul. 18, 2000, and provisional application No. 60/218,863, filed on Jul. 18, 2000.
- (52) **U.S. Cl.** **600/531**; 600/529; 600/532; 600/538

(56) References Cited

U.S. PATENT DOCUMENTS

2.630.798 A	3/1953	White et al.
2,826,912 A		Kritz 73/194
2,831,348 A	4/1958	Kritz 73/861.28
2,838,399 A	6/1958	Vogel, Jr.
2.869.357 A	11/1959	Kritz 73/32

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

DE	198 10 476	9/1998
EP	0459647	12/1991
EP	0 712 638	12/1995
GB	2323292	9/1998
WO	WO 96/40340	12/1996

OTHER PUBLICATIONS

Medical Progress Through Technology, vol. 9, No. 1, 1982 Berlin (D), pp. 27–32, R. Salminen et al., "Computerized Breath–By–Breath Analysis of Respiratory Variables During Exercise."

British Journal Of Anaesthesia, vol. 49, 1977 London (GB) pp. 575–587, J. A. Bushman et al. "Closed Circuit Anaesthesia."

(List continued on next page.)

Primary Examiner—Robert L. Nassar Assistant Examiner—Patricia Mallari (74) Attorney, Agent, or Firm—Gifford, Krass, Groh, Sprinkle, Anderson & Citkowski, P.C.

(57) ABSTRACT

The present invention provides an indirect calorimeter for measuring the metabolic rate of a subject. The calorimeter includes a respiratory calorimeter configured to be supported in contact with the subject so as to pass inhaled and exhaled gases as the subject breathes. A flow pathway is operable to receive and pass inhaled and exhaled gases. A first end of the flow pathway is in fluid communication with the respiratory connector and a second end is in fluid communication with a source and sink for respiratory gases. A flow meter generates electrical signals as a function of the instantaneous flow volume of inhaled and exhaled gases passing through the flow pathway. A component gas concentration sensor generates electrical signals as a function of the instantaneous fraction of a predetermined component gas in the exhaled gases as the gases pass through the flow pathway. A computation unit receives the electrical signals from the flow meter and the component gas concentration sensor and calculates at least one respiratory parameter for the subject as the subject breathes through the calorimeter.

6 Claims, 16 Drawing Sheets

